Dualforce** / Uniforce**

POLYSTYRENE, R-6.6

NON-INSULATED



Every detail guaranteed™

STEEL THICKNESS: 2"



Dualforce / Uniforce

STEEL THICKNESS: 2"

MODEL PATTERNS AND LAYOUTS -

TRADITIONAL

CLASSIC (21" x 13" and 40" x 13")





Classic XI

CARRIAGE HOUSE

NORTH HATLEY (19 3/4" x 15" grouped by 2)





SHAKER-NH (40 1/2" x 15")



WINDOWS (21" X 13" OR 40" X 13") -





Plastic inserts are installed on the exterior side of the window (easy to remove).













Richmond Arch

COLORS



Moka Brown





GENTEK RIJII DING PRODUCTS

Claystone







Widths from 8' to 18', in 1" increments. Heights from 6'6" to 8', in 3" increments. See your garage door dealer for more details on oversized doors available.

CONSTRUCTION



DUAL FORCE

Double-layer: steel + insulation

Single-layer: steel

- 1 24-gauge galvanized steel with a coat of baked-on paint for a high durability door
- 2 DUALFORCE only: Polystyrene insulation is protected with a PVC
- Tongue and groove joints between sections that fit seamlessly

WARRANTY -

Door sections: 15 years (limited) Bolted Hardware: 1 year

Weatherstripping: 1 year

FOR A CARRIAGE HOUSE LOOK. ADD DECORATIVE HARDWARE



For all the available models, visit garaga.com/decorative-hardware.



8500 25th Avenue Saint-Georges, QC G6A 1K5 Canada

418 227-9458 info@garaga.com garaga.com











YOUR **GARAGA DISTRIBUTOR**

For all the available Inserts. visit garaga.com/inserts.